GLASS FIBER PANEL FILTER





Applications:
Pre-filter for ventilation equipment and HVAC
Paint booths

Highlights:
- High dust holding capacity
- Dust / paint holder

Filter Standard:	ISO 16890
Filter Class:	ISO Coarse
Media:	Glass Fiber

Frame:	Cardboard
Rec. Final Pressure Drop EN13053:	Initial ΔP +50 Pa or initial ΔP x3 whichever is lower
Max. Operating Tempature:	80˚C

Filter Model	Filter Class EN 779 (cancelled)	Filter Class ISO 16890	Media Material	Dimensions WxHxD (mm)	Nominal Airflow (m^3/h)	Initial Pressure Drop (Pa)
GC-G3-C-287-592-48	G3	Coarse 45%	Glass Fiber	287x592x48	1700	55
GC-G3-C-592-592-48	G3	Coarse 45%	Glass Fiber	592x592x48	3400	55
GC-G4-C-287-592-96	G4	Coarse 55%	Glass Fiber	287x592x96	1700	70
GC-G4-C-592-592-96	G4	Coarse 55%	Glass Fiber	592x592x96	3400	70
"Differential Pressure Tolerance (±10% + 5 Pa) or (10 Pa + 5 Pa) whichever is greater"						

GLASS FIBER PANEL FILTER CODE CONFIGURATION

Filter Type	Filter Class	Frame	Dimensions (mm)
GC : Glass Fiber Panel Filter	G3 G4	C: Cardboard	592x592x48

